

# Hybrid Inverter

SUN- 3 / 3.6 / 5 / 6 K-SG04LP1-AU



Colorful touch LCD, IP65 protection degree



DC couple and AC couple to retrofit existing solar system

16

Max. 16pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel

140

Max. charging/discharging current of 140A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator

**Deye**

Stock Code: 605117.SH

**JOULE  
POWER**

www.joulepower.com.au

Model	SUN-3K -SG04LP1-24-AU	SUN-3K -SG04LP1-AU	SUN-3.6K -SG04LP1-AU	SUN-5K -SG04LP1-AU	SUN-6K -SG04LP1-AU
<b>Battery Input Data</b>					
Battery Type	Lead-acid or Li-Ion				
Battery Voltage Range (V)	20~30	40~60	40~60	40~60	40~60
Max. Charging Current (A)	140	70	90	120	135
Max. Discharging Current (A)	140	70	90	120	135
Number of battery input	Yes				
Charging Curve	3 Stages / Equalization				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
<b>PV String Input Data</b>					
Max. DC Input Power (W)	3900	3900	4680	6500	7800
Rated PV Input Voltage (V)	370 (100~500)				
Start-up Voltage (V)	125				
MPPT Voltage Range (V)	125~425				
Full Load DC Voltage Range (V)	240~425				
PV Input Current (A)	13		13+13		
Max. PV ISC (A)	17		17+17		
Number of MPPT / Strings per MPPT	1/1		2/1+1		
<b>AC Output Data</b>					
Rated AC Output and UPS Power (W)	3000		3600		6000
Max. AC Output Power (W)	3000		3600		6000
AC Output Rated Current (A)	13		15.7		26.1
Max. AC Current (A)	13		15.7		26.1
Max. Continuous AC Passthrough (A)	35				40
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor	0.8 leading to 0.8 lagging				
Output Frequency and Voltage	50Hz/45Hz-55Hz; L/N/PE 230V/ 195.5V-253V, 240V/204V-264V				
Grid Type	Single Phase				
DC injection current (mA)	THD<3% (Linear load<1.5%)				
<b>Efficiency</b>					
Max. Efficiency	97.60%				
Euro Efficiency	97.00%				
MPPT Efficiency	99.90%				
<b>Protection</b>					
Integrated	PV Input Lightning Protection, Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge protection				
Output Over Voltage Protection	DC Type II/AC Type III				
<b>Certifications and Standards</b>					
Grid Regulation	AS/NZS 4777.2				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
<b>General Data</b>					
Operating Temperature Range ( )	-40~60 , >45 derating				
Cooling	Natural cooling				
Noise (dB)	<30 dB				
Communication with BMS	RS485; CAN				
Weight (kg)	14			15.1	
Size (mm)	330W x 433H x238D				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	5 years				